

1. PRODUCT AND COMPANY IDENTIFICATION

Company

Southern Metal & Plastic Products
3400 Treecourt Industrial Blvd
St.Louis MO 63122

24 Hour Emergency Response Information
(800) 222- 5116

Trade Name: ABS Formliner Sheet

2. COMPOSITION/ INFORMATION ON INGREDIENTS

CAS Number

9003-56-9

9003-54-7

100-42-5

107-13-1

Component

Acrylonitrile/ Butadiene/ Styrene

Styrene/ Acrylonitrile Copolymer

Acrylonitrile/ Butadiene/ Styrene Terpolymer

Residue Acrylonitrile Monomer

3. HAZARDS IDENTIFICATION

Emergency Overview

The ABS sheet is not expected to be an inhalation hazard under normal processing conditions. If material is processed under prolonged exposure to flame or high temperature, thermal burns to the skin may occur, and gases may be produced that are irritating to the respiratory system.

Primary Routes of Exposure

Routes of entry could include eye, skin, and inhalation, due to exposure to flame (molten plastic).

Acute Effects of Exposure due to High Temperature and Thermal Decomposition

At Thermal Decomposition small amounts of Styrene, Ethylbenzene and Acrylonitrile may be emitted. Exposure of high concentrations of these vapors and fumes could cause nausea, drowsiness, and headache.

Chronic Effects of Exposure to High Temperature and Thermal Decomposition

In October 1988, the National Institute for Occupational Safety and Health (NIOSH) found insufficient evidence to classify Styrene as a Carcinogen.

4. FIRST AID MEASURES

Eyes: If there is contact to the eyes with molten material, rinse with plenty of water and seek immediate medical attention. If fumes enter the eye, rinse with water for 15 minutes and seek immediate medical attention if irritation develops.

Skin: If skin has contact with molten, place affected area under cold running water. Seek medical

attention for removal of material from the affected area.

Inhalation: Remove affected individual to fresh air, seek medical attention if difficulties in breathing occurs.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media

Dry extinguisher, water, carbon dioxide, foam

Protective Equipment for Fire-Fighting

Firefighters should be equipped with self-contained breathing apparatus.

Hazardous Combustion Products

During a fire, irritating and toxic gasses and aerosols may be generated by thermal decomposition and combustion.

6. ACCIDENTAL RELEASE MEASURES

The ABS material in sheet form is not applicable for this section.

7. HANDLING AND STORAGE

Handling

Protect against flame and intense heat.

Storage

Store in a well ventilated area, avoid extreme heat and any sources of ignition, or open flames.

Secondary Use/ Reprocessing

When reprocessing material for secondary use, ground all handling equipment. Keep material and dust produced away from heat and flame. Use good housekeeping practices when reprocessing material.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal Protective Equipment

Respiratory Protection

During processing, respiratory protection may not be necessary if ventilation is adequately provided. At excessive processing temperatures, breathing protection may be required.

Hand Protection

Gloves may be required when processing the sheet due to sharp edges and when plastic is in the molten state.

Eye Protection

Safety glasses with side- shields are recommended.

General

Avoid contact with molten material on the skin, eyes and clothing. Handle product in accordance with good industrial hygiene and safety practices.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State and Appearance

Solid ABS Sheet

Flashpoint

730 deg. F- 752 deg F (388 deg C- 400 deg C)

Autoignition Temperature

923 deg. F- 950 deg. F (495 deg. C- 510 deg. C)

Melting Point

180 deg. F- 225deg. F (82deg. C- 107 deg. C)

10. STABILITY AND REACTIVITY

Stability and Reactivity

This product in the finished state (sheet) is stable.

Incompatibility with various substances

Reactive with strong oxidizing agents

Decomposition Temperature

Begins at approximately 500 deg. F (260 deg. C)

Hazardous Decomposition Products

Carbon Dioxide, Water, Carbon Monoxide, Hydrocarbons, Hydrogen cyanide and possibly some original monomers (styrene and acrylonitrile) are released as fumes and vapors when processing the sheet at high temperature and exposure to flame.

11. TOXICOLOGICAL INFORMATION

Chronic Effects on Humans

No specific information is available, but no ecological hazard is suspected.

Other Toxic Effects on Humans

In plastic sheet form, not considered dangerous to humans

12. ECOLOGICAL INFORMATION

No information is available but no ecological hazard is suspected.

13. DISPOSAL CONSIDERATIONS

Waste Information

Transfer to an approved disposal area in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT Classification

Not a DOT controlled or regulated material (U.S.A)

15. REGULATORY INFORMATION

OSHA Classification

This product is hazardous under the criteria of the federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA

Components of this product are listed on the TSCA inventory.

CERCLA

This material is not subject to special reporting under the requirements of the Comprehensive Environment Response, Compensation and Liability Act.

SARA Title III

SECTION 302 Extremely Hazardous Substances.
None reported

Section 311/312 Hazard Categories

Immediate Health Hazard; Delayed Health Hazard

RCRA Status

It is the responsibility of the product user to determine at the time of disposal of the material, if it should be classified as a hazardous waste. (40 CFR 261.2024)

State Regulations

No Proposition 65 chemicals present at level that would require a warning under the California Safe Drinking Water Toxic Enforcement Act.

16. OTHER INFORMATION

Hazardous Material Information System (U.S.A)

Health	1
Fire Hazard	0

Southern Metal & Plastic Products.
MATERIAL SAFETY DATA SHEET
PRODUCT or CHEMICAL NAME
Last Update: 27 June 2007

Pg 5 of 5



Reactivity 0
Personal Protection 0

ABS- Acrylonitrile/ Butadiene/ Styrene Terpolymer

Date Prepared: Feb. 18,2005

The information listed within this MSDS is solely designed for the finished processed sheet. The information listed is to the best of our knowledge, accurate and reliable. However, there is no warranty or guarantee that can be made to its accuracy, reliability or completeness. Primex will not accept liability for any loss or damage that may occur from the use of this information.

Prepared and Approved By: David Wolf
Approval date: Feb. 18, 2005